MATERIAL SAFETY DATA SHEET

HMIS CODES: H F R P PRODUCT NAME: POLYPRIMER SURFACER

PRODUCT CODE: 901 GRAY 2*3 1

========= SECTION I - MANUFACTURER IDENTIFICATION ============

MANUFACTURER'S NAME: PCL

ADDRESS : 3150 E. PICO BLVD.

LOS ANGELES, CA 90023-3683

EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 4/30/2009

INFORMATION PHONE : (800) 672-4900 NAME OF PREPARER:

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRI	
~ STYRENE	100-42-5	4.5	68
OSHA PEL: 100 PPM, ACGIH TLV: 50 PPM			
ACETONE	67-64-1	185.5	68
OSHA PEL: 1000 ppm; 2,400 mg/m3			
OSHA TWA: 750 ppm; 1,800 mg/m3			
OSHA STEL: 1000 ppm; 2,400 mg/m3			
ACGIH TWA: 500 ppm, STEL: 750 ppm			
~ SOLVENT NAPHTHA(PETROLEUM),LT. ALIPHATIC	64742-89-8	41.4	68
OSHA PEL: 400 ppm, ACGIH TLV: 400 ppm			
~ METHYL ISOBUTYL KETONE	108-10-1	14.5	68
OSHA PEL: 100 ppm, ACGIH TLV: 50 ppm			
~ METHYL ETHYL KETONE	78-93-3	70.9	68
OSHA PEL: 200 ppm, ACGIH TLV: 200 ppm			
n-BUTYL ACETATE	123-86-4	8.4	68
ACGIH TLV: 150 ppm			

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING RANGE (Deg F): 133 - 295 DENSITY: 11.14 lb/gal

VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 1.34

ACTUAL CATALYZED COATING V.O.C.: 1.67 lbs/gal; 200 gm/L

ACTUAL CATALYZED MATERIAL V.O.C.: 1.54 lbs/gal; 185 gm/L

SOLUBILITY IN WATER: Negligible EVAPORATION RATE: SLOWER THAN ETHER

APPEARANCE AND ODOR: Gray liquid with mild odor

========= SECTION IV - FIRE AND EXPLOSION HAZARD DATA ============

FLASH POINT (Deg F): 1 METHOD USED: TOC

FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: 1 UPPER: 12.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

Use approved self-contained breathing apparatus. Do not use direct stream of water.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat, sparks or open flames.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea and headache. High concentrations may result in narcosis.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Eye contact: May cause severe irritation, redness, tearing and blurred vision. Skin contact: May cause moderate irritation.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause irritation, de-fatting and dermatitis.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye, nose, respiratory tract and skin irritation, headache, drowsiness and nausea. Ingestion may result in vomiting; aspiration (breathing in) into the lungs may result in aspiration pneumonitis. Chronic: Long term exposure may lead to central nervous system depression, dermatitis and liver and kidney damage.

CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: Yes OSHA REGULATED: No This material contains a cobalt compound, which is classified as a possible carcinogen for humans (2B) by IARC. This material contains styrene, which is classified as a possible carcinogen for humans (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: MOVE PERSON TO FRESH AIR. PROVIDE ARTIFICIAL RESPIRATION OR OXYGEN IF BREATHING IS DIFFICULT. EYE & SKIN CONTACT: FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. WASH AFFECTED AREAS WITH SOAP AND WATER IMMEDIATELY. REMOVE CONTAMINATED CLOTHING. INGESTION: IF SWALLOWED, DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION IMMEDIATELY.

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

PROVIDE VENTILATION. LARGE SPILLS MAY BE SCOOPED UP. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS.

WASTE DISPOSAL METHOD

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from high temperatures and open flames. Keep containers tightly closed. Use with adequate ventilation.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

========= SECTION VIII - CONTROL MEASURES ==============

RESPIRATORY PROTECTION

Use self-contained breathing apparatus where vapor concentration may be above TLV limits. Where vapor does not exceed TLV limits, use NIOSH/MSHA approved respirator.

VENTILATION

Adequate volume and pattern to keep air contaminant concentration below current applicable OSHA or ACGIH TLV limits.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Chemical goggles, safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

DOT (GROUND)

1.3 gallons (5 liters) or less:

UN1263, Paint, 3, PGII, "Ltd. Qty."

Greater than 1.3 gallons (5 liters): UN1263, Paint, 3, PGII

AIR

UN1263, Paint, 3, PGII

CALIFORNIA PROPOSITION 65

None

The information contained herein is based on the data available to us and is believed to be correct. However, PCL makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. PCL assumes no responsibility for injury from the use of the product described herein.