

M A T E R I A L S A F E T Y D A T A S H E E T

PRODUCT NAME: SPEEDPRIME SURFACER HIGH-BUILD GRAY
 PRODUCT CODE: 913

HMIS CODES: H F R P
 2*3 2

===== SECTION I - MANUFACTURER IDENTIFICATION =====

MANUFACTURER'S NAME: PACIFIC COAST LACQUER
 ADDRESS : 3150 E. PICO BLVD.
 LOS ANGELES, CA 90023-3683
 EMERGENCY PHONE(CHEMTREC) : (800) 424-9300 DATE PRINTED : 04/20/07
 INFORMATION PHONE : (800) 672-4900 NAME OF PREPARER : N/A

===== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =====

| REPORTABLE COMPONENTS | CAS NUMBER | VAPOR PRESSURE mmHG | WEIGHT @TEMP(F) | PERCENT |
|---|------------|------------------------|--------------------|---------|
| ACETONE | 67-64-1 | 185.5 | 68 | 19 |
| OSHA PEL: 1000 ppm; 2,400 mg/m3 | | | | |
| OSHA TWA: 750 ppm; 1,800 mg/m3 | | | | |
| OSHA STEL: 1000 ppm; 2,400 mg/m3 | | | | |
| ACGIH TWA: 500 ppm, STEL: 750 ppm | | | | |
| ~ PARACHLOROBENZOTRIFLUORIDE | 98-56-6 | 5.3 | 68 | 16.88 |
| OSHA PEL: NE, ACGIH TLV: NE | | | | |
| TITANIUM DIOXIDE (as total nuisance dust) | 13463-67-7 | NA | NA | 4 |
| OSHA PEL: 10 ppm, ACGIH TLV: 10 mg/m3 | | | | |
| ~ ISOPROPYL ALCOHOL, 2-PROPANOL | 67-63-0 | 32 | 68 | 3.01 |
| OSHA PEL: 400 ppm, ACGIH TLV: 400 ppm | | | | |
| ~ XYLENE | 1330-20-7 | 6.1 | 68 | 2.06 |
| OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm | | | | |
| ~ DI(2-ETHYLHEXYL)PHTHALATE | 117-81-7 | 0 | 68 | 1.68 |
| OSHA PEL: 5 MG/M3, ACGIH TLV: 5 MG/M3 | | | | |
| ~ METHYL PROPYL KETONE | 107-87-9 | 28 | 68 | 1.40 |
| OSHA PEL: 200 ppm, ACGIH TLV: 200 ppm | | | | |
| DIBASIC ESTER(CAS #1119-40-0,627-93-0,106-65-0)MIXTURE | | .2 | 68 | 1 |
| OSHA PEL: N/E, ACGIH TLV: N/E | | | | |
| SOLVENT NAPTHA,HEAVY AROMATIC | 64742-94-5 | 7.5 | 68 | 1.3 |
| OSHA TWA: NE, ACGIH STEL: NE, SUPPLIER RECOMMENDED TWA: 100 PPM | | | | |
| METHYL AMYL KETONE , 2-HEPTANONE | 110-43-0 | 2.14 | 68 | 1 |
| ACGIH TLV: 50 ppm | | | | |
| ~ ETHYL BENZENE | 100-41-4 | 10 | 68 | 0.31 |
| OSHA PEL: 100 ppm, ACGIH TLV: 100 ppm | | | | |
| PROPYLENE GLYCOL METHYL ETHER ACETATE | 108-65-6 | 3.7 | 68 | 0.2 |
| OSHA PEL: N/E, ACGIH TLV: N/E | | | | |
| CARBON BLACK(as unbound particles of carbon) | 1333-86-4 | NA | NA | 0.14 |

~Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

===== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS =====

BOILING RANGE (Deg F): 133 - 723 DENSITY: 10.41 lb/gl
 VAPOR DENSITY: HEAVIER THAN AIR SPECIFIC GRAVITY (H2O=1): 1.25
 COATING V.O.C.: 2.06 lb/gl MATERIAL V.O.C.: 1.11 lb/gl
 COATING V.O.C.: 247 g/l MATERIAL V.O.C.: 133 g/l
 SOLUBILITY IN WATER: Negligible EVAPORATION RATE: SLOWER THAN ETHER
 APPEARANCE AND ODOR: Gray liquid with mild odor

===== SECTION IV - FIRE AND EXPLOSION HAZARD DATA =====

FLASH POINT (Deg F): 1 METHOD USED: TOC
 FLAMMABLE LIMITS IN AIR BY % VOLUME- LOWER: .3 UPPER: 12.8

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL, WATER FOG, OTHER

SPECIAL FIREFIGHTING PROCEDURES

Use approved self-contained breathing apparatus. Do not use direct stream of water.

UNUSUAL FIRE AND EXPLOSION HAZARDS

Fire-exposed containers should be cooled with water to prevent pressure build-up which could result in container rupture.

===== SECTION V - REACTIVITY DATA =====

STABILITY: STABLE

CONDITIONS TO AVOID

Excessive heat, sparks or open flames.

INCOMPATIBILITY (MATERIALS TO AVOID)

Strong oxidizing agents,alkaline materials.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

Thermal decomposition may yield carbon dioxide and/or carbon monoxide,nitrogen oxides,methane and carboxylic acids.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

===== SECTION VI - HEALTH HAZARD DATA =====

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Inhalation: May cause irritation to nose, throat and respiratory tract. High vapor concentrations may cause CNS depression.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin and eye contact: May cause irritation to both.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Skin absorption: May cause irritation.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Ingestion: May cause vomiting which can result in aspiration of liquid into lungs. Do not induce vomiting.

HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute: May cause eye, skin, nose and respiratory tract irritation. Early to moderate CNS depression may be evidenced by giddiness, headache, nausea and dizziness. Aspiration of liquid into the lungs can result in aspiration pneumonitis which may be evidenced by coughing and labored breathing. Chronic: Prolonged and repeated contact with skin may cause defatting and drying of the skin which may result in dermatitis.

CARCINOGENICITY: NTP CARCINOGEN: Yes IARC MONOGRAPHS: Yes OSHA REGULATED: No

This material contains Di(2-ethylhexyl) phthalate, which is classified as a possible carcinogen for humans (2B) by IARC and NTP. This material contains ethylbenzene which is classified as "possibly carcinogenic to humans" (2B) by IARC. This material contains carbon black, which is classified as a possible carcinogen for humans (2B) by IARC.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Pre-existing eye, skin and respiratory disorders may be aggravated.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR. IF BREATHING STOPS, GIVE ARTIFICIAL RESPIRATION. SPLASH (EYES): FLUSH EYES IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. SPLASH (SKIN): WASH AFFECTED AREAS WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DO NOT INDUCE VOMITING. IF VOMITING OCCURS SPONTANEOUSLY, KEEP HEAD BELOW HIPS TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. GET MEDICAL ATTENTION IMMEDIATELY.

===== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL SOURCES OF IGNITION AND PROVIDE VENTILATION. LARGE SPILLS MAY BE PICKED UP WITH NON-SPARKING TOOLS. SMALL SPILLS MAY BE PICKED UP WITH ABSORBENT MATERIALS. ADD WATER TO CONTAINERS. DO NOT ALLOW MATERIALS TO BECOME DRY.

WASTE DISPOSAL METHOD

Place in tightly closed containers and dispose of in accordance with local, state and federal regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Store away from heat, sparks and open flames. Keep containers tightly closed when not in use. Use with adequate ventilation. Electrically bond and ground the drum while emptying. Do not allow contents to become dry.

OTHER PRECAUTIONS

Do not take internally. Avoid prolonged contact. Ground equipment to prevent accumulation of static charge.

===== SECTION VIII - CONTROL MEASURES =====

RESPIRATORY PROTECTION

Use a NIOSH-approved respirator if exposure exceeds TLV limits.

VENTILATION

Use explosion-proof ventilation as required to control vapor concentrations.

PROTECTIVE GLOVES

Chemical resistant gloves

EYE PROTECTION

Chemical goggles, safety glasses

OTHER PROTECTIVE CLOTHING OR EQUIPMENT

Eye bath and safety shower

WORK/HYGIENIC PRACTICES

Wash hands thoroughly before eating or using the washroom. Smoke in smoking areas only.

===== SECTION IX - REGULATORY INFORMATION =====

CALIFORNIA PROPOSITION 65

This product contains a chemical known to the State of California to cause cancer.

Contains: Carbon Black - Di(2-ethylhexyl) Phthalate - Ethylbenzene -

===== SECTION X - DISCLAIMER =====

The information contained herein is based on the data available to us and is believed to be correct. However, Pacific Coast Lacquer Co. makes no warranty expressed or implied regarding the accuracy of these data or the results to be obtained from the use thereof. Pacific Coast Lacquer Co. assumes no responsibility for injury from the use of the product described herein.